SPECIFICATION DATA

Skylight Fall Protection Screens

The PRS Domed Skylight Fall Protection Screen provides permanent fall protection at skylights and does not penetrate the roof membrane. “Zero Penetration” attachment will not damage roof flashings, prevents moisture from entering the building, and will not void the roof warranty. Galvanized screens install quickly and easily to ensure long-term performance, safety and compliance. PRS Domed Skylight Fall Protection Screen meets and exceeds numerous Standards and requirements for skylight openings and insures OSHA compliance.

Key Features

- 3” x 4” hot dipped galvanized welded wire mesh
- Extrueded aluminum mounting rails
- “Zero Penetration” mounting
- Fast and easy installation

Installation

PRS Domed Skylight Screens can be installed on both new and existing acrylic dome skylight units. Standard installation allows mounting to the skylight frame without penetrating the roof membrane.

Materials

Screen	3” x 4” welded wire mesh, .195”diameter x 3/8” steel plate (ASTM
Extrusion	Outdoor PVC, extruded
Retaining Clips	Stainless Steel
Finish	Galvanized ASTM A123Horizontal Rails
Hardware	Galvanized 3/4” #12 hex washer head self-drilling screws.

Size

8’ wide x unlimited length

Weight

1.5 LB/sf

Standards

Meets and exceeds OHSA standard CFR 29 1926.501, CFR 29 1910.23, Cal-OSHA §3212(e), ANSI/ASSE A1264.1-2007 section 3.4.

Warranty

Manufactures limited waranty covers any defects from 1 year of purchase date

1345 Taney Street
North Kansas City, MO 64116
T 888.990.2990 | F 816.472.0822