



# R2000™

## Mobile Fall Protection



www.leadingedgesafety.net  
(888) 990.2990

## Frequently Asked Questions




### WHERE ARE THE COUNTERWEIGHTS AND/OR WATER TANKS?

The R2000™ has no counterweights to add or water tanks to fill. The solid steel frame along with the downforce of the safety engagement arm eliminates the need for counterweights and water tanks.



### HOW DOES IT WORK?

If a fall were to occur, the R2000™ has a patented roof safety engagement device which penetrates the roof. This creates a secure anchor point to arrest the fall.



### HOW MANY MEN CAN ATTACH TO THE R2000™?

Two men can attach to the R2000™ for fall arrest protection.\* Two additional men can attach to the TriRex™ for fall restraint for a total of five men attached at any one time.

*\*For CONCRETE, only one man can attach for fall arrest.*



### IS THE R2000™ OSHA APPROVED?

The R2000™ is manufactured in compliance with OSHA regulation 1926.502(d) for fall arrest anchors.



### WHERE DO I HOOK UP TO ON THE R2000™?

Two rings are welded to a green plate located in the center on the side of the R2000™. These are the fall arrest tie-off points. Two yellow swiveling d-rings are tie-offs for fall restraint. The four yellow fixed lifting hooks located on the corners are for hoisting purposes only.



### CAN THE BASE MODEL BE USED WITHOUT THE LARGE JOB BOX

NO-The large job box is an integral part of the R2000™ and is bolted to the frame.



### WHAT TYPE OF TIRES ARE INSTALLED ON THE TRIREX™?

All R200™ models come standard with solid polyurethane tires.



# R2000™

## Mobile Fall Protection



www.leadingedgesafety.net  
(888) 990.2990

## Frequently Asked Questions



### ARE THERE ANY PARTS THAT NEED TO BE REPLACED OR RECERTIFIED AFTER FALL ARREST?

Although the R2000™ can be used after again after a fall arrest, it's a good idea to replace the claw components. We've got you covered with our Pivot Point Replacement Kit.

The **Pivot Point Replacement Kit** contains a new pivot pin, brass bushings and a washer and cotter pin.



### HOW MUCH DOES THE R2000™ WEIGH?

The empty weight of the base model R2000™ with solid tires weighs 763lbs.



### CAN I INSTALL MY OWN EQUIPMENT ON THE R2000™?

Yes—Leading Edge Safety offers an optional 12 cubic foot job box but the base model is sold without any additional equipment. The owner has the opportunity to install their own equipment.

*\*For CONCRETE, only one man can attach for fall arrest.*



### CAN THE ENGAGEMENT SYSTEM BE INSTALLED ON THE ROOFING CARTS I ALREADY OWN?

NO—The R2000™ is specifically designed and tested to operate in combination with the roof safety engagement device. A fabricated roofing cart does not comply with OSHA regulations without proper testing and certification.



### HOW DO I PURCHASE A R2000™?

Leading Edge Safety has a number of established resellers throughout the United States and Canada. To find a dealer near you, please visit our website:

<http://www.leadingedgesafety.net/locations>