



Frequently Asked Questions



WHERE ARE THE COUNTERWEIGHTS AND/OR WATER TANKS?

The Stinger™ uses 12 removeable counterweights. This allows for the added convenience of moving the unit. The Stinger™ will fit in the bed of a truck, through doorways, in elevators and through roof hatches.



HOW DOES IT WORK?

If a fall were to occur, the Stinger™ has a patented roof safety engagement device which penetrates the roof. This creates a secure anchor point to arrest the fall.



HOW MANY MEN CAN ATTACH TO THE STINGER™?

One man can attach to the Stinger™ for fall arrest protection. One additional man can attach to the Stinger™ for fall restraint for a total of two men attached at any one time.



IS THE STINGER™ OSHA APPROVED?

The Stinger™ is manufactured in compliance with OSHA regulation 1926.502(d) for fall arrest anchors.



WHERE DO I HOOK UP TO ON THE STINGER™?

One ring is welded to a green plate located in the center on the side of the Stinger™. This is the fall arrest tie-off point. One yellow swiveling d-ring hook is the tie-off for fall restraint.



CAN THE RAPTOR RESCUE™ BE USED WITH THE STINGER™?

Yes—the Raptor Rescue wench and pole retrieval system can be used to rescue a fallen worker.



WHAT TYPE OF TIRES ARE INSTALLED ON THE TRIREX™?

All Stinger™ models come standard with solid polyurethane tires.



Frequently Asked Questions



ARE THERE ANY PARTS THAT NEED TO BE REPLACED OR RECERTIFIED AFTER FALL ARREST?

Although the Stinger™ can be used again after a fall arrest, it's a good idea to replace the claw components. We've got you covered with our Pivot Point Replacement Kit.

The **Pivot Point Replacement Kit** contains a new pivot pin, brass bushings and a washer and cotter pin.



HOW MUCH DOES THE STINGER™ AND IT'S WEIGHTS WEIGH?

The frame weight of the base model Stinger™ with solid tires weighs 126lbs. Each of the 12 counterweights weighs 50 LBS.



CAN I INSTALL MY OWN EQUIPMENT ON THE STINGER™?

Yes-Leading Edge Safety offers the optional Raptor Rescue™ system, but the base model is sold without any additional equipment. The owner has the opportunity to install their own equipment.



CAN THE ENGAGEMENT SYSTEM BE INSTALLED ON THE ROOFING CARTS I ALREADY OWN?

NO-The Stinger™ engagement arm is specifically designed and tested to operate in combination with the roof safety engagement device. A fabricated roofing cart does not comply with OSHA regulations without proper testing and certification.



HOW DO I PURCHASE A STINGER™?

Leading Edge Safety has a number of established resellers throughout the United States and Canada. To find a dealer near you, please visit our website:

<http://www.leadingedgesafety.net/locations>